

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Substance
Trade name	: UN1307 Xylene (isomers ) GLR
Chemical name	: xylene
IUPAC name	: xylene
EC Index-No.	: 601-022-00-9
EC-No.	: 215-535-7
CAS-No.	: 1330-20-7
REACH registration No	: 01-2119488216-32
Product code	: XYLN-00P
Formula	: C6H4(CH3)2

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Laboratory use

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

labbox labware s.l.  
Migjorn, 1  
P.O. Box Barcelona (SPAIN)  
08338 Premia de Dalt – SPAIN  
ES  
T +34 937 07 79 70 - F +34 937 909 532  
[info@labbox.com](mailto:info@labbox.com) - [www.labbox.com](http://www.labbox.com)

**1.4. Emergency telephone number**

Emergency number : +34 937 077 970 (For technical information\_Office Hours) In case of medical emergency phone 112 or to your local emergency number.

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3	H226
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhal.), Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H and EUH statements: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : H226 - Flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H312+H332 - Harmful in contact with skin or if inhaled.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.
- : P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 - Do NOT induce vomiting.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

## 2.3. Other hazards

PBT: not relevant – no registration required

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Substance type : Multi-constituent

Name	Product identifier	%
Xylene	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	75 – 100

### 3.2. Mixtures

Not applicable

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing. Do not remove clothing if it sticks to the skin. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Never give anything by mouth to an unconscious person.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: ABC-powder.
Unsuitable extinguishing media	: Strong water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic vapours are released.

#### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Use personal protective equipment as required.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: This material and its container must be disposed of in a safe way, and as per local legislation. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Heading 8. For further information refer to section 13.

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Keep containers closed.
Precautions for safe handling	: Ensure good ventilation of the work station.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep container tightly closed.
Storage area	: Store in a well-ventilated place. Store in a cool, well-ventilated place. Keep away from food and drink. Store away from heat. Avoid the build-up of electrostatic charge.
Special rules on packaging	: Keep only in original container.

#### 7.3. Specific end use(s)

Laboratory chemicals.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

UN1307 Xylene (isomers ) GLR (1330-20-7)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
<b>France - Occupational Exposure Limits</b>	
Local name	Xylène, isomères mixtes, purs
VME (OEL TWA)	221 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	50 ppm
VLE (OEL Ceiling/STEL)	442 mg/m <sup>3</sup>
VLE (OEL Ceiling/STEL) [ppm]	100 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Xylol (alle Isomeren)
AGW (OEL TWA) [1]	440 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	100 ppm
Remark	DFG,EU,H
<b>Italy - Occupational Exposure Limits</b>	
Local name	Xilene, isomeri misti, puro
OEL TWA	221 mg/m <sup>3</sup>

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

UN1307 Xylene (isomers ) GLR (1330-20-7)	
OEL TWA [ppm]	50 ppm
OEL STEL	442 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Portugal - Occupational Exposure Limits	
Local name	Xileno (isómeros )
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Spain - Occupational Exposure Limits	
Local name	Xilenos, mezcla isómeros
VLA-ED (OEL TWA) [1]	221 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL)	442 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	100 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA [1]	220 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL TWA [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL	441 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL STEL (ppm)	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

UN1307 Xylene (isomers ) GLR (1330-20-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	289 mg/m <sup>3</sup>
Acute - local effects, inhalation	289 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

UN1307 Xylene (isomers ) GLR (1330-20-7)	
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	174 mg/m <sup>3</sup>
Acute - local effects, inhalation	174 mg/m <sup>3</sup>
Long-term - systemic effects, oral	1,6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14,8 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,327 mg/l
PNEC aqua (marine water)	0,327 mg/l
PNEC aqua (intermittent, freshwater)	0,327 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2,31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6,58 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

EN 374. Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

#### Eye protection:

Face shield

Eye protection			
Type	Field of application	Characteristics	Standard
Category II			EN 166, EN 167, EN 168

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.2. Skin protection

#### Skin and body protection:

Chemical resistant safety shoes

Skin and body protection	
Type	Standard
Safety shoes	EN ISO 13287, EN ISO 20345, EN 13832-1

#### Hand protection:

Wear protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Category III					EN ISO 374-1, EN 420

#### Other skin protection

#### Materials for protective clothing:

Wear protective clothing

Other skin protection Materials for protective clothing		
Condition	Material	Standard
		EN 1149-1, EN 1149-2, EN 1149-3, EN 13034, EN ISO 13982-1, EN ISO 6529, EN ISO 6530, EN 464

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Use respiratory protection

Respiratory protection			
Device	Filter type	Condition	Standard
filtering face piece	with filter for vapors/gases		EN 405

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Transparent.
Molecular mass	: 106,17 g/mol

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour	: characteristic.
Odour threshold	: Not available
Melting point	: -39 °C
Freezing point	: Not available
Boiling point	: 137 – 140 °C
Flammability	: Not available
Lower explosion limit	: 0,8 vol %
Upper explosion limit	: 6,7 vol %
Flash point	: 27 – 32 °C
Auto-ignition temperature	: 488 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: > 0,84 mm <sup>2</sup> /s
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Partition coefficient n-octanol/water (Log Pow)	: 3,12 – 3,2
Vapour pressure	: 820 Pa
Vapour pressure at 50 °C	: Not available
Density	: 0,865 – 0,875 kg/m <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20 °C	: 3,7
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 100 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable in use and storage conditions as recommended in item 7.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Direct sunlight.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

On exposure to high temperature, may decompose, releasing corrosive gases.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Harmful if inhaled.



# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

UN1307 Xylene (isomers ) GLR (1330-20-7)	
LD50 oral rat	2100 mg/kg
LD50 dermal rat	1100 mg/kg
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 inhalation rat (mg/l)	11 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

UN1307 Xylene (isomers ) GLR (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

Aspiration hazard : May be fatal if swallowed and enters airways.

UN1307 Xylene (isomers ) GLR (1330-20-7)	
Viscosity, kinematic	> 0,84 mm <sup>2</sup> /s

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : Not applicable

#### 11.2.2. Other information

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

UN1307 Xylene (isomers ) GLR (1330-20-7)	
LC50 - Fish [1]	2,6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Daphnia [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 - Other aquatic organisms [1]	0,6 mg/l
EC50 72h - Algae [1]	10 mg/l
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

### 12.2. Persistence and degradability

UN1307 Xylene (isomers ) GLR (1330-20-7)	
Biodegradation	88 %

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.3. Bioaccumulative potential

#### UN1307 Xylene (isomers ) GLR (1330-20-7)

Partition coefficient n-octanol/water (Log Pow)	3,12 – 3,2
---	------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### UN1307 Xylene (isomers ) GLR (1330-20-7)

PBT: not relevant – no registration required

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Not applicable.

### 12.7. Other adverse effects

Other adverse effects : Do not discharge into drains or rivers.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Must follow special treatment according to local regulation.
European List of Waste (LoW) code	: 14 06 03* - other solvents and solvent mixtures
HP Code	: HP3 - "Flammable:" — flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; — flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; — flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; — flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; — water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR)	: UN 1307
UN-No. (IMDG)	: UN 1307

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

UN-No. (IATA) : UN 1307  
UN-No. (ADN) : UN 1307  
UN-No. (RID) : UN 1307

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : XYLENES  
Proper Shipping Name (IMDG) : XYLENES  
Proper Shipping Name (IATA) : Xylenes  
Proper Shipping Name (ADN) : XYLENES  
Proper Shipping Name (RID) : XYLENES  
Transport document description (ADR) : UN 1307 XYLENES, 3, III, (D/E)  
Transport document description (IMDG) : UN 1307 XYLENES, 3, III (23°C c.c.)  
Transport document description (IATA) : UN 1307 Xylenes, 3, III  
Transport document description (ADN) : UN 1307 XYLENES, 3, III  
Transport document description (RID) : UN 1307 XYLENES, 3, III

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Danger labels (IATA) : 3



#### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3



#### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3



# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: III
Packing group (RID)	: III


### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: 3YE

#### Transport by sea

Special provisions (IMDG)	: 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Flash point (IMDG)	: 23°C to 30°C c.c.
Properties and observations (IMDG)	: Colourless liquids. Flashpoint: 23°C to 30°C c.c. Explosive limits: 1.1% to 7% Immiscible with water.

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3.	UN1307 Xylene (isomers ) GLR
3(a)	UN1307 Xylene (isomers ) GLR
3(b)	UN1307 Xylene (isomers ) GLR
40.	UN1307 Xylene (isomers ) GLR

##### REACH Annex XIV (Authorisation List)

UN1307 Xylene (isomers ) GLR is not on the REACH Annex XIV List

##### REACH Candidate List (SVHC)

UN1307 Xylene (isomers ) GLR is not on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

UN1307 Xylene (isomers ) GLR is not subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

##### POP Regulation (Persistent Organic Pollutants)

UN1307 Xylene (isomers ) GLR is not subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

##### Ozone Regulation (1005/2009)

Xylene is not subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### VOC Directive (2004/42)

VOC content : 100 %

### Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

### Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

### 15.1.2. National regulations

#### France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

#### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to VwVwS, Annex 1 or 2; ID No. 206).  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed  
SZW-lijst van mutagene stoffen : The substance is not listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Xylene is listed

#### Denmark

Class for fire hazard : Class II-1  
Store unit : 5 liter  
Classification remarks : R10 <H226;H304;H312+H332;H315;H319;H335;H373;H412>; Emergency management guidelines for the storage of flammable liquids must be followed  
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3

# UN1307 Xylene (isomers ) GLR

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.